

TECHNICAL DATA SHEET

www.tycoident.com

Document number: TTDS-099
Issue: 4
Date: July 2006

1966

Thermal Transfer Ribbon

DESCRIPTION:	Ultra-High Performance black thermal transfer ribbon that produces the ultimate in print permanence. For use on a specified range of Tyco Electronics identification products. Ideal for use in environments where the marker may come into contact with abrasion, solvent or chemical attack.
APPLICABLE PRINTERS/ PRODUCTS:	T212M: HX-SCE, D-SCE, HLXNEL T312M: HX-SCE, D-SCE, HX, HLX, HXTM-FB, & CM-SCE-TP
SHELF LIFE	12 months when stored between -5°C (23°F) and 40°C (104°F)
COLOUR	Black
DIMENSIONS:	300m x 100mm (984' x 3.9") for 1966-RIBBON 74m x 100mm (242' x 3.9") for T200-RIBBON-1966
WINDING DIRECTION	Ink side out
ORDERING INFORMATION	1966-RIBBON for T312M T200-RIBBON-1966 for T212M
PRINT PERFORMANCE	See individual product technical data sheets

Page 1 of 1

Business locations:

☎ N America: + 1 650 361 3860 (West Coast)
☎ France: +33 (0) 476 099696 (Labels)
☎ Germany: + 49 (0) 6074 89080
☎ UK: + 44 (0) 1495 244000 (Labels)
☎ Japan: + 81 (0) 44 900 5102

☎ N America: + 1 401 751 6505 (East Coast)
☎ France: + 33 (0) 134 20 21 22 (Other products)
☎ UK: + 44 (0) 1793 528171 (Other products)
☎ Singapore: + 65 (0) 4866 151

All the above information, including illustrations, is believed to be reliable. Users, however, should independently evaluate the suitability of each product for their application. Tyco Electronics makes no warranties as to the accuracy or completeness of the information and disclaims any liability regarding its use. Tyco Electronics only obligations are those in the Standard Terms and Conditions of Sale for this product and in no case will Tyco Electronics be liable for any incidental, indirect or consequential damages arising from the sale, resale, use or misuse of the product. Tyco Electronics Specifications are subject to change without notice. In addition Tyco Electronics reserves the right to make changes in materials or processing, without notification to the Buyer, which do not affect compliance with any applicable specification.